NOTES: UNLESS OTHERWISE SPECIFIED 1. MAKE FROM: MULBERRY P/N: 97152 BLANK DOUBLE GANG USING STANDARD BARBARA MOUNTING HOLES PER DIÁGRAM. EQUIVALENT WALLPLATE MAY BE PROVIDED THAT MOUNTING HOLES MEETS MULBERRY OR THE DRAWING DIMENSIONS. 2. THREE CUTOUTS TO BE FILLED WITH CATEGORY 5 JACKS FROM: HUBBELL PREMISE WIRING INC. OR ACCEPTED EQUIVALANT P/N HUBBELL 5110816, 8 PIN, CATEGORY 5e 568A JACK OR EQUAL SANTA3. DIMENSIONS LISTED ARE NOMINAL AND MAY BE ALTERED SCRIBE .18 HIGH (TYPICAL) AS NECESSARY, PROVIDED THAT SUCH DEVIATIONS ALLOW --| .5600 |--- LOCATE APPROXIMATELY WHERE SHOWN A MINIMUM FIT TOLERANCE BETWEEN JACK LISTED ABOVE AND THE CUTOUTS WITHOUT MOUNTING CLIPS OR SPRING TENSION CALIFORNIA INSERTS. 4. DEBURR OR BREAK ALL SHARP EDGES. ₩ UCSB1 5. INSCRIBE WALLPLATE AS NOTED. ø.375 DRILL 6. MANUFACTURER IS TO PROVIDE SAMPLE MODEL OF THIS WALLPLATE FOR APPROVAL/ACCEPTANCE PRIOR TO COMPLETION OF ORDER. UNIVERSITY .7500 VOICE DATA 1 .6800 4.5000 CUTOUTS FILLED W/PLUGS BB/CATV DATA 2 .6200 ø.1875 DRILL 4 PLCS 1.825 4.5000 10/26/99 UCSB STANDARD WALL PLATE FOR LEVEL 5 CABLE FILE: WP3JACK & 8-PIN EIA/TIA 568A CATEGORY 5e MODULAR JACK